




ADTESU Rental LED Display




*Cabinet size


RVPP3





5 5 5With a special heat dissipation structure, the heat dissipation is excellent. Fanless design, absolutely silent operation.





Using point-by-point correction technology, brightness and chromaticity are consistent.

A wide viewing angle gives your screen the largest viewing area.

Specifications			
Pixel pitch	3.9 mm	Brightness	400-850 cd/m² (adjustable)
Module Size (W*H)	250 mm x 250 mm x 13 mm	Contrast ratio	5000:1
Physical density	65,536 pixel/m ²	Color temperature	3200K - 9300K
Module resolution (W*H)	64x64	Brightness uniformity	> 97%
Module weight	0.54 Kg	Color uniformity	> 97%
Module port	HUB-HD01	Light pixel centerline spacing difference	< 3%
Driving Method	Constant current 1/16scan	Single pix brightness correction	(support)
LED encapsulation	Commercial Grade 3-in-1 SMD2121 (Black)	Gray scale/color	≥ 16.7 M color
Module working voltage	4.2-5 VDC	LED lifetime: typical	100000 hours
Module maximum power consumption	35 W	Cabinet weight	7 Kg
Viewing angle	160°/160°	Cabinet flatness	≤ 0.1 mm
Module of cabinet (W*H)	2 x 2	Cabinet size (WxH)	500 mm x 500 mm x 80 mm
Cabinet resolution (W*H)	128x128	Maximum power	140 W/m²
Distance option	1-30m	Display working voltage	100 - 240 V AC 50/60 Hz
Frame rate	60Hz / 120Hz (3D)	Working environment temperature	(-10) ~ 60°C
Refresh rate	3840Hz Adjustable	Working environment humadity (RH)	10% ~ 70%