

Wired Conference System



AM-3000

≡ Product introduction:

AM-3000 series is designed for simple conference room, it is a highly stable conference system with easy operation.

≡ Features:

- Up to 100 units can be connected to one system, maximum 12 chairman units. It can be expanded to 250 units with expanding device.
- Meeting Mode: FIFO/ LIFO, Chairman Mode, All On.
- Unit voice activation.
- With camera tracking function, supports various camera agreements, agreement can be customized upon request.
- Compatible with central controller via RS-232.
- Unit hot-plug connection available.

≡ Features of microphone unit:

- Hyper-cardioid directional condenser capsule.
- 60cm voice pick-up distance.
- Anti-interference from cellphone.
- Detachable design.
- With earphone output.



Specifications of AM-3000M

| | |
|--------------------------|-------------------|
| Power Supply | AC110V - 240V |
| Max. Current Consumption | 1A |
| Frequency Response | 50Hz - 20KHz |
| SNR | >85dBA |
| Distortion | <0.05% |
| Dimension | 483 x 323 x 90 mm |
| Weight | 5.5Kg |
| Color | Black |



Specifications of AM-3000C/D

| | |
|--------------------------|-------------------------------------|
| Power Supply | DC24V |
| Max. Current Consumption | 40mA |
| Sensitivity | -46dB/Pa |
| Frequency Response | 100Hz - 12KHz |
| SNR | >75dB |
| Distortion | <0.1% |
| Dimension | 170 x 115 x 44 mm; Mic Tube : 420mm |
| Weight | 0.85Kg |
| Color | Black |